

Description

Part Number: SW2391

Features:

- T304 16GA Stainless Steel Construction
- Triple 3Ø, 30A 480V IP67/69, 4/4X Mechanical Interlock with On/Off LED. UL Listed.
- 20A, 125V black weather resistant duplex GFCI with extra duty non metallic rain-tight in use cover
- Removable lid and rear access panel
- Pre-drilled mounting holes and access cutout for underground conduit entry in base
- Pre-installed watertight conduit hub. No Drilling!
- 27.5”L x 11.4”D x 48”H
- Ships fully assembled

Picture



Applications

Winery

- Crush Pad
- Bottling
- Cellar

Food Processing

Agriculture

Dairy

Shipping Ports

Boat Docks

Rail Yards

Wind & Solar

Technical Data

Mechanical Interlock

Current: 30A

Voltage: 3Ø, 480V

Frequency: 60Hz

Switch Horsepower: 20HP

Clock Position: 7h (red)

Material: Glass Reinforced Polyester

Temp Rating: -40°F to 140°F

Ingress Protection: IP66/IP67/IP69
NEMA type 3R, 4/4X, 12

Safety: Dual mechanical interlock
On/Off LED
OSHA Lockout/Tagout compliant

Impact Protection: IK10 (20J)

Standards: UL508 (non-fused)
UL60947-4-1

