



# EMI/RFI Filter Solutions



Series:	PA	PB	PASP	PF	PBH
<b>Voltage:</b>	115/250V	115/250V	115/250V	115/250V	115/250V
<b>Current:</b>	1A, 2A, 3A, 6A, 8A, 10A, 15A	1A, 2A, 3A, 6A, 8A, 10A, 15A	1A, 2A, 3A, 6A, 8A, 10A, 15A	1A, 3A, 5A, 6A, 10A	16A, 20A
<b>Options:</b>	Flange	Flange, Snap-in	Flange, PC mount	PC mount	Flange, Snap-in
<b>Leakage Current:</b>	0.45mA, 250V	0.45mA, 250V	0.45mA, 250V	0.8mA, 250V	0.5mA, 250V
<b>Hipot Rating:</b>					
<b>L to G</b>	2250VDC	2250VDC	2250VDC	2250VDC	2250VDC
<b>L to L</b>	1450VDC	1450VDC	1450VDC	1450VDC	1450VDC
<b>Contacts:</b>	Wire, QC, Solder	Wire, QC, Solder	PCB Pin, Solder	PCB Pin	Wire, QC, Solder
<b>Temperature:</b>	-25°C to 110°C	-25°C to 110°C	-25°C to 110°C	-25°C to 85°C	-25°C to 110°C




Series:	HGN-336	HGN-337	HGN-339	HGN-341	HGN-375(A,B,C)
<b>Voltage:</b>	115/250V	125/250V	125/250V	125/250V	115/250V
<b>Current:</b>	1A, 2A, 3A, 4A, 6A	1A, 2A, 3A, 4A, 6A	1A, 2A, 3A, 4A, 6A	1A, 2A, 3A, 4A, 6A	1A, 2A, 3A, 4A, 6A, 10A
<b>Options:</b>	Snap-in/Switch	Snap-in/Fused/Switch	Snap-in/Fused/Switch Voltage Select	Snap-in/Fused/Switch Voltage Select	Snap-in/Flange Fused/Switch
<b>Leakage Current:</b>	0.5mA, 250V	0.5mA, 250V	0.5mA, 250V	0.5mA, 250V	1.0mA, 250V
<b>Hipot Rating:</b>					
<b>L to G</b>	2250VDC	2250VDC	2250VDC	2250VDC	2250VDC
<b>L to L</b>	1450VDC	1450VDC	1450VDC	1450VDC	1450VDC
<b>Contacts:</b>	QC	QC	QC	QC	Wire, QC, Solder
<b>Temperature:</b>	-25°C to 85°C	-25°C to 85°C	-25°C to 85°C	-25°C to 85°C	-25°C to 110°C



# EMI/RFI Filter Solutions



Series:	HGN-365A	HGN-368A	HGN-369	PG
<b>Voltage:</b>	115/250V	115/250V	115/250V	115/250V
<b>Current:</b>	1A, 2A, 3A, 4A, 6A, 8A, 10A	1A, 2A, 3A, 6A, 8A, 10A, 15A	1A, 2A, 3A, 4A, 6A,	1A, 3A, 6A, 10A
<b>Options:</b>	Snap-in/Flanged Fused/IP 65	Flange/Switch	Flange, Fused	Chassis Single Stage
<b>Leakage Current:</b>	0.5mA, 250V	0.45mA, 250V	0.5mA, 250V	0.8mA, 250V
<b>Hipot Rating:</b>				
<b>L to G</b>	2250VDC	2250VDC	2250VDC	2250VDC
<b>L to L</b>	1450VDC	1450VDC	1450VDC	1450VDC
<b>Contacts:</b>	Wire, QC, Solder	QC, Solder	Solder	Wire, Solder
<b>Temperature:</b>	-25°C to 110°C	-25°C to 110°C	-25°C to 85°C	-25°C to 85°C



Series:	PE3P4W	PC/PD	PEA/PK	PEM	PE
<b>Voltage:</b>	115/250V	115/250V	115/250V	115/250V	115/250V
<b>Current:</b>	10A-250A	1A, 3A, 5A, 6A, 10A, 15A, 20A	1A, 2A, 3A, 5A, 6A, 10A, 15A, 20A, 30A	1A, 2A, 3A, 4A, 5A, 6A, 10A, 20A	5A, 10A, 15A, 20A, 30A
<b>Options:</b>	Chassis 3 Phase	Chassis Single or Dual Stage	Chassis Single Stage	Chassis Single or Dual Stage	Chassis Single or Dual Stage
<b>Leakage Current:</b>	0.9mA, 2.0mA	0.8mA, 250V	0.45mA, 250V	0.45mA, 250V	0.8mA, 250V
<b>Hipot Rating:</b>					
<b>L to G</b>	2250VDC	2250VDC	2250VDC	2250VDC	2250VDC
<b>L to L</b>	1450VDC	1450VDC	1450VDC	1450VDC	1450VDC
<b>Contacts:</b>	Screw	QC, Screw	Wire, QC, Screw	QC, Screw	QC, Screw
<b>Temperature:</b>	-25°C to 110°C	-25°C to 110°C	-25°C to 110°C	-25°C to 110°C	-25°C to 110°C